

**In the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**5    Listing of Claims:**

1.    (Currently amended) A cleaning machine for cleaning a surface in which cleaning solution is distributed to the surface and substantially simultaneously extracted along with the dirt on the surface in a continuous operation as it moves along the surface  
10    comprising:
  - a)    a base assembly for movement along the surface;
  - b)    a liquid distribution system associated with said base assembly for distributing the cleaning solution to the cleaning surface;
  - c)    a suction nozzle assembly mounted to said base assembly, said suction  
15    nozzle assembly including a front nozzle portion and rear nozzle portion, said front nozzle portion defining a fluid flow path having an inlet opening and an outlet opening, said rear nozzle portion defining a fluid flow path having an inlet opening and an outlet opening;
  - d)    a suction source in fluid communication with said suction nozzle for  
20    applying suction to draw the cleaning solution and dirt from the surface and through the suction nozzle assembly; ~~and~~
  - e)    a valve assembly is associated with said suction nozzle assembly, said valve assembly substantially covering said outlet of said front nozzle portion to close said fluid flow path of said front nozzle portion in response to said base  
25    assembly moving in one of the forward direction and rear direction, said valve assembly substantially covering said outlet of said rear nozzle portion to close said fluid flow path of said rear nozzle portion in response to said base assembly moving in other one of the forward direction and rear direction;
  - f)    a handle portion pivotally connected to said base assembly, said liquid  
30    distribution system including a solution tank for holding the cleaning

solution, said solution tank being removably mounted to one of said base assembly and said handle portion, a liquid distribution system further including a distributor fluidly connected to said solution tank for distributing the cleaning solution to the surface.

- 5
2. (Original) The cleaning machine of claim 1 including a rotatable brush assembly positioned intermediate said front and rear nozzle portions.
3. (Original) The cleaning machine of claim 1 wherein said fluid flow path of said rear  
10 nozzle portion is open upon said valve assembly covering said outlet of said front nozzle portion to close said fluid flow path of said front nozzle portion, said fluid flow of said front nozzle portion being open upon said valve assembly covering said outlet of said rear nozzle portion to close said fluid flow path of said rear nozzle portion.
- 15
4. (Original) The cleaning machine of claim 3 wherein said valve assembly includes a valve part movable between a first position that covers said outlet of said front nozzle portion to close said fluid flow path of said front nozzle portion in response to said base assembly moving in the forward direction and a second position that covers  
20 said outlet of said rear nozzle portion to close said fluid flow path of said rear nozzle portion in response to said base assembly moving in the rear direction.
5. Canceled.
- 25
6. (Currently Amended) The cleaning machine of claim [[5]] 1 including a recovery tank removably mounted to one of said handle and said base assembly, said recovery tank in fluid communication with said suction nozzle for collecting the cleaning solution and dirt drawn through the suction nozzle assembly.
- 30
7. (Currently Amended) ~~The cleaning machine of claim 1~~ A cleaning machine for cleaning a surface in which cleaning solution is distributed to the surface and

substantially simultaneously extracted along with the dirt on the surface in a continuous operation as it moves along the surface comprising:

- a) a base assembly for movement along the surface;
  - b) a liquid distribution system associated with said base assembly for distributing the cleaning solution to the cleaning surface;
  - c) a suction nozzle assembly mounted to said base assembly, said suction nozzle assembly including a front nozzle portion and rear nozzle portion, said front nozzle portion defining a fluid flow path having an inlet opening and an outlet opening, said rear nozzle portion defining a fluid flow path having an inlet opening and an outlet opening;
  - d) a suction source in fluid communication with said suction nozzle for applying suction to draw the cleaning solution and dirt from the surface and through the suction nozzle assembly;
  - e) a valve assembly is associated with said suction nozzle assembly, said valve assembly substantially covering said outlet of said front nozzle portion to close said fluid flow path of said front nozzle portion in response to said base assembly moving in one of the forward direction and rear direction, said valve assembly substantially covering said outlet of said rear nozzle portion to close said fluid flow path of said rear nozzle portion in response to said base assembly moving in other one of the forward direction and rear direction; and
  - f) wherein said liquid distribution system includes a first source providing a supply of a first cleaning solution and a second source providing a supply of a second cleaning solution, said liquid distribution system further including at least one front distributor and one rear distributor, one of said front distributor and said rear distributor dispensing said first cleaning solution and other one of said front distributor and said rear distributor dispensing said second cleaning solution.
8. (Original) The cleaning machine of claim 7 including a rotatable brush assembly positioned intermediate said front and rear distributors.

9. (Original) The cleaning machine of claim 7 wherein said front distributor dispenses the first cleaning solution in response to said base assembly moving in the forward direction, said rear distributor dispensing said second cleaning solution in response to said base assembly moving in the rear direction..
10. The cleaning machine of claim 9 wherein said rear distributor does not dispense the cleaning solution in response to said base assembly moving in the forward direction and said front distributor does not dispense the cleaning solution in response to the base assembly moving in the rear direction.
- ~~10~~11. (Currently Amended) The cleaning machine of claim 9 wherein said first cleaning liquid solution is detergent and water and said second cleaning ~~fluid~~ solution is clean water.
- ~~11~~12. (Currently Amended) The cleaning machine of claim 1 wherein said liquid distribution system further includes at least one front distributor and one rear distributor, one of said front distributor and said rear distributor dispensing said cleaning solution in response to said base assembly moving in the forward direction and other one of said front distributor and said rear distributor dispensing said cleaning solution in response to said base assembly moving in the rear direction.
- ~~12~~13. (Currently Amended) The cleaning machine of claim 9 wherein said rear distributor does not dispense the cleaning solution in response to said base assembly moving in the forward direction and said front distributor does not dispense the cleaning solution in response to the base assembly moving in the rear direction.
- ~~13~~14. (Currently Amended) The cleaning machine of claim 9 including a rotatable brush assembly positioned intermediate said front and rear distributors.
- ~~14~~15. (Currently Amended) A cleaning machine for cleaning a surface in which cleaning

solution is distributed to the surface and substantially simultaneously extracted along with the dirt on the surface in a continuous operation as it moves along the surface comprising:

- a) a base assembly for movement along the surface;
- 5 b) a liquid distribution system associated with said base assembly for distributing the cleaning solution to the cleaning surface;
- c) a suction nozzle assembly mounted to said base assembly, said suction nozzle assembly including a front nozzle portion and rear nozzle portion, said front nozzle portion defining a fluid flow path having an inlet opening and an outlet opening, said rear nozzle defining a fluid flow path having an inlet opening and an outlet opening;
- 10 d) a suction source in fluid communication with said suction nozzle for applying suction to draw the cleaning solution and dirt from the surface and through the suction nozzle assembly; and
- 15 e) wherein said liquid distribution system further includes at least one front distributor and one rear distributor.

~~15~~16. (Withdrawn) The cleaning machine of claim ~~14~~ 15 wherein one of said front distributor and said rear distributor dispensing said cleaning solution in response to said base assembly moving in the forward direction and other one of said front distributor and said rear distributor dispensing said cleaning solution in response to said base assembly moving in the rear direction.

20

~~16~~17. (Withdrawn) The cleaning machine of claim ~~15~~ 16 wherein the fluid flow path of said front nozzle portion is closed in response to said base assembly moving in one of the forward direction and rear direction, the fluid flow path of said rear nozzle portion being closed in response to said base assembly moving in other one of the forward and rear direction.

25

~~17~~18. (Withdrawn) The cleaning machine of claim ~~15~~ 16 wherein said liquid distribution system includes a first source providing a supply of a first cleaning solution and a

30

second source providing a supply of a second cleaning solution, one of said front distributor and said rear distributor dispensing said first cleaning solution and other one of said front distributor and said rear distributor dispensing said second cleaning solution.

5

~~18~~19. (Withdrawn) The cleaning machine of claim 17 wherein said front distributor dispenses the first cleaning solution in response to said base assembly moving in the first direction said rear distributor dispensing said second cleaning solution in response to said base assembly moving in the second direction.

10

~~19~~20. (Withdrawn) A cleaning machine for cleaning a surface in which cleaning solution is distributed to the surface and substantially simultaneously extracted along with the dirt on the surface in a continuous operation as it moves along the surface comprising:

15

- a) a base assembly for movement along the surface;
- b) a liquid distribution system associated with said base assembly for distributing the cleaning solution to the cleaning surface;
- c) a suction nozzle assembly mounted to said base assembly;
- d) a suction source in fluid communication with said suction nozzle for applying suction to draw the cleaning solution and dirt from the surface and through the suction nozzle assembly; and
- e) wherein said liquid distribution system includes at least one front distributor and one rear distributor, one of said front distributor and said rear distributor dispensing said cleaning solution in response to said base assembly moving in a first direction and other one of said front distributor and said rear distributor dispensing said cleaning solution in response to said base assembly moving in the second direction.

20

25

30

~~20~~21. (Withdrawn) The cleaning machine of claim ~~19~~ 20 including an agitator positioned intermediate the front and rear distributors.

- 5      ~~21~~22. (Withdrawn) The cleaning machine of claim ~~19~~ 20 wherein said liquid distribution system further includes a first source providing a supply of a first cleaning solution and a second source providing a supply of a second cleaning solution, wherein said front distributor dispenses the first cleaning solution in response to said base assembly moving in the first direction, said rear distributor dispensing said second cleaning solution in response to said base assembly moving in the second direction.